

HEATING MODE

Model	: PERS.122M
Outdoor side heat exchanger	: Air
Indoor side heat exchanger	: Air
Type	: Compressor driven vapour compression
Driver of the compressor	: Electric Motor

Rated heating capacity [kW] - $P_{rated,h}$	72,39
Seasonal space heating energy efficiency [%] - $\eta_{s,h}$	133,4
Seasonal coefficient of performance - SCOP	3,41
Sound power level, outdoor [dB] - L_{WA}	86

Declared heating capacity for part load at given outdoor temperatures T_j and indoor 20°C (Dry bulb)		
Pdh		
	Value	Unit
$T_j = -7\text{ °C}$	50,68	[kW]
$T_j = +2\text{ °C}$	40,32	[kW]
$T_j = +7\text{ °C}$	32,96	[kW]
$T_j = +12\text{ °C}$	37,38	[kW]
$T_j = T_{biv}\text{ °C}$	55,31	[kW]
$T_j = T_{ol}\text{ °C}$	46,91	[kW]
If $TOL < -20\text{ °C}$, $T_j = -15\text{ °C}$ (for air-to-water (brine) heat pumps)	-	[kW]

Declared efficiency of performance for part load at given outdoor temperature T_j and indoor 20°C (Dry bulb)		
COP _d		
	Value	Unit
$T_j = -7\text{ °C}$	2,80	[kW]
$T_j = +2\text{ °C}$	3,78	[kW]
$T_j = +7\text{ °C}$	4,33	[kW]
$T_j = +12\text{ °C}$	4,89	[kW]
$T_j = T_{biv}\text{ °C}$	2,93	[kW]
$T_j = T_{ol}\text{ °C}$	2,65	[kW]
If $TOL < -20\text{ °C}$, $T_j = -15\text{ °C}$ (for air-to-water (brine) heat pumps)	-	[kW]

Bivalent temperature	T_{biv}	-2	°C
Degradation coefficient, for each part load condition where it is relevant ¹	Cd_h	0,25	

Power input in modes other than active mode								
Off mode	[kW]	P _{OFF}	0,00		Crankcase heater mode	[kW]	P _{CK}	0,18
Thermostat-off mode	[kW]	P _{TO}	0,02		Standby mode	[kW]	P _{SB}	0,04
Supplementary heater					Heating capacity	[kW]	elbu	28,94
					Type of energy input		Electric	
Capacity control					Staged			
GWP of the refrigerant, kg CO ₂ eq [100 years]					466			
For air-to-air air conditioner: air flow rate, outdoor measured [m ³ /h]					39441			

İmbat Soğutma Isıtma Makina Sanayi ve Ticaret A.Ş
KOSBİ Mh, 62. Sk. no:14, 35371 Kemalpaşa/İzmir
Pbx: +90 232 877 21 01
www.imbat.com

¹ If Cd_h is not determined by measurement then the default degradation coefficient air conditioners shall be 0,25.